

- 1. Press the <Machine Status> button.
- 2. Check the machine's IP address on the [Machine Information] screen.



[PC] Installing the Print Driver

 You can get the print driver by heading to (<u>https://support-fb.fujifilm.com/setupSupport.do</u>) And searching for your printer's model. Then select you macs operating system

← → C a support-tb.fujfim.com/setupSupport.do	DesuCentre V 0227E Drivers & Devenlande
FUL/FILM Business Innovation Home Join our Team FUL/FILM BL Direct New Zealand Globs	Not your product? Search again
Solutions & Insights Products Support & Sustainability Company Contact	
Home - Support & Drivers Support & Drivers	Drivers Self Help Documentation Utilities Learning
Enter product name or number           Docucentre-v c3375         Search         > Which product do I have?           > Error Code Search         > Error Code Search         > Easy Setup Download	Operating Mac OS 11.0 v Language English v Help with Driver Selection System

4. Make sure to select the driver type: PS

Mac Print Driver > Version: 1.73.108 Compatibility > File Information >	
Notes —— Driver Type: PS	

- The print driver for Mac OS X supports Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, OS X 10.8 Mountain Lion, OS X 10.9 Mavericks, and OS X 10.10 Yosemite, OS X 10.11 El Capitan.
- 6. To install the print driver for Mac OS X, login as a user with administrator rights.
- Double-click the [Fuji Xerox Print Driver for Mac OS X Installer] icon in [Software] > [MacPrinter] > [MacOSX] > [Common].

	14 12 10 14 2 1 20 10 10 10 10 10 10 10 10 10 10 10 10 10	
	1 of 2 tandated	
Salking Street Several State	ret.embary	
Non-CEX Column (egg)		

8. Click [Continue]. Confirm the Software License Agreement, and then click [Continue].



## Mac Guide – Adding A New Printer - Harcourts

	😻 Batlah Fué Xerur Print Oniver for Mac 05 X		Butterfi Fugi Xerue Print Driver for Mac 05 X
	Welcome to the Pull Xerrer Print Oniver for Marc OS 8 Installer		Boltware Lizonse Agreement
<ul> <li>Entroduction</li> <li>Convex</li> <li>Destination Type</li> <li>Encontrol Type</li> <li>Encontrol Type</li> <li>Sciencesy</li> </ul>	You will be guiled through the state recessory to install the otherse.	<ul> <li>Introduction</li> <li>License</li> <li>Institution Solari.</li> <li>Institution Type</li> <li>Institution</li> <li>Recently</li> <li>Recently</li> </ul>	

9. Click [Agree]. Click [Continue].



10. Click [Install]. And enter [Username] and [Password] and click [Install Software].

Introduction     Lisense     Lisense     Lisense     Mustimation Salact     Mustimation     Mustimation     Mustimation     Mustimation	Renderd inset or "Nacimpol H0.55 IT  Renderd Inset also 'Nacimpol H0.55 IT  This set? Table 5.6 MB influence on your computer  Chick inset to partners a strated inset of this computer will be adde to use this software.	Installer is trying to install new software. Type your password to allow this. Username. Password:
	Change I mult Location. Ge lines	Cancel Install Software

11. Click [Close].

[PC] Adding a printer

12. Open [System Preferences] from the [Apple] menu and select [Printers & Scanners], then Click [+].



13. Click [IP] on the displayed window. And enter the machine's IP address in [Address



(9±	Add 1. Second databet	And Control Co
	- 100	Indexes (190.8.2.1 Postcat: Uno Finter Dearcor - URD
Narmi Location Une		Nerrie 190.8.2.1 Loonint Mee E

14. Select [Select Printer Software] for [Use] and Select [DocuCentre-V C3375 T2] from the list of the available drivers, and then click [OK].

A B ATCAN	G 10	ø
Alterner (10.6.5.1) Detertan sens o Rostras Redeal (via Printe Denice) (10		
Series Laws Law Mr of Law and	ne znihole zier Male 200 X yl W	
Parme: 100.0.0.1		
Vocania Anti Select		

15. Click [Ok].



- 16. This window will pop up and you want to make sure you change everything to look like the settings in here. Start off by ticking [Hard Disk] box, followed by changing the [Output Options] to [Finisher Type C3], then tick the [Right Bottom Tray (Booklet Maker)], and then click [OK].
- 17. And now Click [Add Printer] to add the printer, now it's ready to print